



safe-T-seat Assembly Instructions

Parts List

T-bar



Bracket



Hex Key



Cap Screws (2)



Ring Pin



Clip



IMPORTANT: This bicycle carrier must be installed in strict accordance with the instructions provided. The instructions should be read carefully and each step followed carefully and completely.

1. Remove the seat from the box and set it on a carpeted floor. Unlatch the lap bar and pivot it up. Place your child in the seat and adjust the height of the 3 point buckle so the buckle is 2 inches below the child's chin. Adjust each shoulder strap so that it is snug on the child's shoulders and lock the shoulder strap into place with the jam buckles.




2. Take the child out of the seat and looking at the bottom of the seat, remove the assembled T-bar and bracket from the seat plate by removing the ring pin and clip. Then remove 1 cap screw from the bracket.



3. Place the partially assembled pieces around the handlebar stem and insert the other screw. Again, make sure the arrow and the hollow part of the T-bar are facing up. (It may be necessary to raise the handle bar stem to accommodate the T-bar assembly.)



4. Tighten both screws the same length with the hex key so there is even pressure on the bracket. Before tightening the screws completely, make sure the T-bar is aligned with the tire & frame. **Do Not over tighten.**



5. Slide seat onto T-bar as far forward as possible. Secure the T-bar to the seat plate by sliding the ring pin through the holes. Fasten the ring pin with the clip. Never place a child in the seat until ALL parts are secured properly. The seat will not slide on the T-bar when the seat is fastened correctly. There may be some wobble of the seat on the T-bar and this is normal.



6. Holding onto the bike, unlock the lap bar and pivot it up. Put the child in the seat and pull each strap over the child's shoulders and lock into the buckle. Push down the lap bar until it locks.

7. Enjoy your ride!!!

Failure to comply with these manufacturer's instructions can lead to serious injury of the passenger/rider!

WARNINGS, CAUTIONS, NOTICES and TIPS

WHEN USING YOUR BICYCLE CHILD CARRIER

WARNING

1. This child carrier is designed to carry children that weigh up to 38 lbs. - 17 kgs. **DO NOT** carry a child that weighs more than this weight.
2. The rider and the child being carried should wear helmets that meet nationally recognized standards for bicycle helmets.
3. **DO NOT** carry a child, who is less than 12 months of age, in this child carrier. To be a passenger, the child must be able to sit up straight with the head held upright while wearing a bicycle helmet. A doctor should be consulted about any child who of questionable development age.
4. **DO NOT** use this child carrier on rough or off-road conditions.
5. **DO NOT** make any modifications to this child carrier.
6. **DO NOT** permit any part of the child's body or clothing, shoelaces, etc. to come in contact with the moving parts of the bicycle.
7. **DO NOT** permit the child to carry refreshments, food or toys while riding in the child carrier. These items may distract the cyclist and if thrown by the child, they may cause loss of control of the bicycle.
8. ALWAYS attach the security harness snugly around the child.
9. **DO NOT** leave the child unattended in the child carrier.
10. **DO NOT** leave the child in the child carrier when the bicycle is supported only by the kickstand.

CAUTION

1. AVOID riding in inclement or hazardous conditions, including temperatures below freezing that could cause the child to suffer frostbite.
2. Additional luggage or accessories should not be attached to the bicycle child carrier. If additional loads are to be carried on the bicycle, they should be placed only in carriers designed specifically for that purpose.
3. When the child carrier is not in use, buckle the security straps together to prevent the straps from dangling or presenting a hazard to the bicyclist.
4. Before each ride, ensure that the mounted child carrier does not interfere with the cyclist's ability to brake, pedal or steer the bicycle.
5. When riding the bike without the seat attached, remove the T-bar from the bike.

NOTICE

1. Any load added to a bicycle will lessen the stability of the bicycle and alter its riding characteristics. Do not attempt to carry a load that is heavier than you can readily control. Match the load to your weight, strength, and size.
2. Keep these instructions handy for reference when moving the bicycle child carrier to another bicycle or doing maintenance or making adjustments to the bicycle.
3. The bicycle, to which the child carrier is attached, must be in good working order, of a type appropriate for the additional load and of a proper size and adjustment for the rider. The cyclist should consult the information supplied with the bicycle or obtain information from the manufacturer or supplier of the bicycle to determine how to make the necessary adjustments. A properly sized and adjusted bicycle will improve both the comfort and safety of the ride.
4. Before each use, check to determine that all fasteners are in place and secure. Check them frequently and ensure that they have not loosened due to vibration.
5. Always remove the child carrier from the bicycle when the bicycle is being transported on a motor vehicle. This is necessary because the force of the high wind on the child carrier, may degrade or damage the carrier to the point where it may not perform reliably. This carrier has been designed for easy and rapid removal from the bicycle. When reattaching the child carrier, check all fasteners and tighten as required.

TIPS

1. Carry extra clothing for your child, such as a windbreaker, sweater, etc. You are active while cycling, the child is inactive and may feel cooler than you do.
2. Carry an air pump and repair kit, complete with all the necessary tools (including the hex key), to repair a tire or tighten nuts, bolts, etc.
3. Young children are very sensitive to the UV rays from the sun. You can reduce the damaging effects of the sun's UV rays by wearing appropriate clothing, applying sunscreen lotions, and wearing UV protective sunglasses.

WARNING: TO AVOID SERIOUS INJURY, Never, never, ever leave child unattended. Always maintain positive control of the bike. Never, ever use the kickstand alone to support the bike or leave the bike leaning against a support with the child in the seat.

safe-T-seat Pad Assembly Instructions

1. Unbuckle the shoulder straps from the crotch strap buckle.
2. Slide the crotch strap through the slot in the bottom of the pad.
3. Insert the 3 push pins through the 3 holes in the seat pad and fasten them into the 3 holes in the backrest of the safe-T-seat.
4. Do not leave the safe-T-seat attached to your bike while transporting the bike with your car. You will lose the pins and possibly the pad due to wind.
5. Enjoy the ride!!



safe-T-seat Steering Wheel Assembly (Optional Accessory)

Parts List

Fender Washer



Nylock Nut



3/4" Bolt



1/2" Bolt (3)



Wing Nuts (3)



Face pad



Tools Required - Philips screwdriver, 3/8" wrench

1. Take the 3/4" bolt and put it through the front of the steering wheel. Then put the steering wheel onto the base and add the fender washer and the nylock nut. The metal portion of the nut screws onto the bolt and the nylon portion of the bolt will be facing out. Using the wrench and screwdriver, tighten the nut enough so the steering wheel turns with a small amount of friction but not too tight that the child cannot turn the wheel. The steering wheel should not freely turn on its own. The bolt needs to be screwed in to the nylock portion of the nut or the nut will not lock onto the bolt.
2. Peel the paper from the steering wheel pad and attach to the center of the steering wheel.
3. Attach the steering wheel base to the lap bar and align the 3 holes.
4. Screw in the (3) 1/2" bolts until the ends are just flush with the steering base holes.
5. Hold the wing nuts over the screw ends and continue tightening the bolts until tight.
6. The two clamps on the back of the steering wheel base will hold a 1/4" hex wrench.



Accessories and parts available at www.ibertinc.com/order-online

iBert Limited Warranty

This Limited Warranty is the only warranty for your safe-T-seat. There are no other express warranties. The manufacturer warrants this product to be free of manufacturing defects for a period of two years from the date of purchase. This Limited Warranty extends only to the original consumer and is not transferable to anyone else.

This Limited Warranty is limited solely to defects in materials and workmanship and does not cover normal wear and tear or any damage, failure, or loss that is caused by improper assembly, maintenance, adjustment, storage, or use of the safe-T-seat. This Limited Warranty will be void if the safe-T-seat is ever:

- * used in a manner other than for recreation or transportation;
- * modified in any way;
- * rented;
- * used in a manner contrary to the instructions.

The manufacturer is not liable for incidental or consequential loss nor damage due directly or indirectly from the use of this product.

Your prompt registration verifies your right to protection under the terms and conditions of your warranty and returning the card guarantees you'll receive all information and new accessory offers your purchase makes you eligible for.

SPARE T-BAR ASSEMBLIES and replacement parts are available directly from iBert Inc.

Orders can be placed through our website: www.ibertinc.com, by email at: info@ibertinc.com, by fax to 801-302-8518, or by telephone to 801-440-4024.

Made in the USA

U.S. Patent No. 7,044,051